# **J Royal's H4 Compliant Compounds**



### **H4 COMPLIANT COMPOUNDS**

| John Deere<br>Designation | ASTM<br>Type/Class | Description                          | J Royal<br>Compound # |
|---------------------------|--------------------|--------------------------------------|-----------------------|
| JDM H4A                   | BG                 | 70 durometer nitrile                 | N-7011                |
| JDM H4B                   | BG                 | 90 durometer nitrile                 | N-9037                |
| JDM H4C                   | СН                 | 75 durometer nitrile, peroxide cured | N-7504                |
| JDM H4D                   | СН                 | 90 durometer nitrile, peroxide cured | N-9022                |
| JDM H4F                   | СН                 | 75 durometer HNBR, also meets H4C    | N-7505                |
| JDM H4G                   | СН                 | 90 durometer HNBR, also meets H4D    | N-9039                |
| JDM H4J                   | GE                 | under development                    | TBD                   |
| JDM H4N                   | BA                 | under development                    | TBD                   |
| JDM H4P                   | HK                 | 75 durometer Viton™                  | F-7029                |
| JDM H4R                   | HK                 | 90 durometer Viton™                  | F-9010                |

The John Deere® H4 (JDM H4) material specification is one of the rubber sealing industry's most popular material requirements. The specification was developed and is maintained by Deere & Company.

At its core, H4 delineates specific requirements for rubber compounds used to produce O-Rings in various materials. Depending on the material, it addresses conditions and fluids common to the agricultural industry. For example, it includes requirements for exposure to IRM Reference Oils 901 and 903, antifreeze/water mixtures, fuel, and brake fluid. It also incorporates high and low temperature evaluation using H4-specific test methods. JDM H4 requires rigorous evaluation on O-Rings, whose additional requirements include 1000 hour compression set testing of O-Rings with various cross-sections, as well as air conditioning refrigerant/ lubricating oil resistance.

J Royal's H4 compliant compounds are fully tested against all elements of the JDM H4 specification, however they have not been independently certified by Deere & Company. Visit www.jroyal.com/JDMH4 for our latest information.





## Why Industry Leaders Rely on J Royal

#### **GLOBAL REACH – LOCAL RELATIONSHIPS**

For over 60 years, J Royal has provided quality sealing solutions to a diverse group of markets. Our knowledgeable staff is highly regarded in the industry for its ability to consistently provide optimal design recommendations and its commitment to building long-standing, prosperous relationships. What sets J Royal apart is its broad product base, unbeatable product knowledge, extensive logistics and distribution capabilities, and progressive engineering skills, all supported by global resources.

#### A TRUSTED LEADER IN INDUSTRY AND AGRICULTURE

For decades J Royal has been an industry forerunner in the industrial and agricultural marketplace, serving the needs of equipment manufacturers where O-Rings, seals and custom rubber products are crucial.

#### WE'VE GOT WHAT YOU NEED

We supply and stock the widest selection of seals from partner manufacturers around the world. Our vendors are renowned for their engineering and quality programs and we have excellent, long term relationships with them. Even in periods of short supply, we can deliver. We can customize any seal precisely to your specifications.

#### **EXTENSIVE VALUE ADDED SERVICES**

We provide JIT/Kanban programs, pre-production and kitting, special marking and packaging options and much more.

#### FRIENDLY CUSTOMER SERVICE AND EXPERT ON-PREMISE SUPPORT

You're in the best circles with our customer service team. If you need expertise in any area, we've got it, including materials, design, prototyping, testing and more.





NORTH CAROLINA CORPORATE OFFICE 2441 Salem Park Drive Winston-Salem, NC 27127 336.794.0400 PHONE 800.626.8807 TOLL FREE 336.794.0401 FAX ALABAMA 180 Twin Creek Drive Tallassee, AL 36078 336.794.0400 PHONE 800.626.8807 TOLL FREE 336.794.0401 FAX

© 2014, J Royal Co., Inc. Rev 5.17

LIMITED WARRANTY J Royal Co. ["Seller"] warrants that its products ["Goods"] will perform in accordance with their specifications; that the goods will be free from manufacturing defects for a period of twelve [12] months from the date of delivery of the goods to Buyer; and that the goods will be as specified by Buyer in the purchase order. Seller should have the right to elect to either refund the purchase price for any defective goods, provided that the goods were used in the manner for which they were manufactured. Seller does not warrant that the goods are fit for any particular purpose. Seller should have no obligation to refund the purchase price or replace goods that are rendered defective by a Buyer or a third party after they leave Seller's place of shipment.

LIMITED LIABILITY Seller's liability for its goods is limited to their terms set forth in Seller's express warranty set for above, in no event shall Seller's liability exceed the total purchase order price. Seller is not assuming any liability for any indirect, collateral, special, incidental or consequential losses or damages suffered by Buyer, or by any end-user or other third party, including but not limited to, lost profits, loss of business reputation and/or lost business opportunity, for any possible cause of action or claim arising out of or related to the goods sold to Buyer, even if Seller has been advised of the possibility of such loss or damage.